



1 2 Water

- 1. INLET: 1.5 METRE HOSE WITH 3/4" B.S.P. FEMALE TERMINATION 2°C MIN TO 65°C MAX. 2.0 TO 6.0 BAR.
- 2. OUTLET: 1.5 METRE HOSE WITH 3/4" B.S.P. FEMALE TERMINATION

WATER SUPPLY TO HAVE INDEPENDENT ISOLATING VALVE

3 4 Drain

- 3. PUMPED DRAIN: 1/2" BARBED FITTING FOR CONNECTION TO HOSE (NOT SUPPLIED) AND THEN TO A 40m.m. TRAPPED STANDPIPE AT 700m.m. A.F.F.L.
- 4. OVERFLOW: 1/2" BARBED FITTING. (THIS IS FOR A VISIBLE SIGN OF ANY OVERFLOW AND SHOULD NOT BE CONNECTED IN SUCH A WAY AS NOT TO BE VISIBLE)

5 Electric Loading

230/50/1 30watt
13 AMP FUSED SPUR.

2 METRE CABLE SUPPLIED.

SPECIAL NOTE:
ELECTRICAL INSTALLATIONS SHOULD COMPLY WITH CURRENT BS REGULATIONS.

Notes

NOMINAL SALT CAPACITY 10kg
SALT TABLETS ONLY
NOT GRANULAR OR POWDER

RIGHT TO MAKE NECESSARY CHANGES IS RESERVED